

Red Laser Diode

Application

Industrial use / Biomedical

Property

Wavelength $\lambda = 635$ nm

Output Power = 10mW

Package Type = ϕ 5.6mm

Introduction

Egismos currently markets AlGaInP based red laser diodes in the 635nm ~ 670nm wavelengths range. The low operating current and high temperature of the laser diodes are achieved through using misoriented substrate and MQW (Strain compensated) active layer. Egismos laser diodes are highly rated in a broad range of applications including, but not limited to, laser pointers, green lasers, blue laser DVD, laser barcode scanners, diode laser equipments, medical instruments and aerospace applications.



Red Laser Diode Key features

Absolute Maximum Rating at Tc=25℃				
Items	Symbols	Values	Unit	
Optical Output Power	Po(CW)	10	mW	
Reverse Voltage	V	2	V	
Operating Temperature	То	-10~+50	$^{\circ}$ C	
Storage Temperature	Ts	-10~+70	$^{\circ}$	

Electrical and Optical Characteristics at Tc=25 $^\circ$ C					С	
Item	Symbols	Min	Тур.	Max.	Unit	Condition
Optical Output Power	Ро	-	-	10	mW	-
Threshold Current	Ith	-	35	40	mA	-
Operating Current	lop	-	55	65	mA	Po=10mW
Operating Voltage	Vop	-	2.2	2.5	V	Po=10mW
Peak Wavelength	λр	630	635	640	nm	Po=10mW



Dcc no: EG-QS-T-PM-ST-0017 Form no: EG-QR-T-QA-0003 Date:160818

<u>EGISMOS</u>	635nm Laser Diode			D	<u>6-5-635-10</u>	
Beam Divergence	$\theta_{\prime\prime}$	6	7.5	11	deg	Po=10mW
beam bivergence	θ \perp	30	33	38	deg	Po=10mW

Electrical Connection(Bottom	Package Type	
View]		
Unit (mm) Bottom View	PD LD	
Package Drawing		
1.2±0.1 6.5±0.1	2.3±0.1 1.0±0.1 2.3±0.1 2.3±0.1 2.3±0.1 2.3±0.1 2.3±0.1 2.3±0.1	

Specifications are subject to change without notice.





Dcc no: EG-QS-T-PM-ST-0017 Form no: EG-QR-T-QA-0003 Date:160818